

AMENDMENTS TO THE CLAIMS

The following claim set replaces all prior versions, and listings, of claims in the application:

1. (CANCELLED).

2. (CURRENTLY AMENDED) An image display device as set forth in Claim 28
1, further comprising:

~~a sensor for sensing the light characteristics of the external light,~~
wherein the chrominance signal converter converts the chrominance signal into a chrominance signal of a color suitable for an output of the sensor.

3. (CURRENTLY AMENDED) An ~~The~~ image display device as ~~set forth in~~
~~Claim 2,~~ wherein comprising:

119 an image display section for displaying an image in accordance with an input of a chrominance signal; and

a chrominance signal converter for converting the chrominance signal to be inputted into the image display section, in accordance with light characteristics of external light incident upon the image display section, the chrominance signal converter including includes a target display color setting section which uses information regarding the light characteristics of the external light to generate a target display color chrominance signal indicative of for setting a color to display on the image display section for providing as an image which agrees agreeable with human chromatic adaptation characteristics of human, according to the output of the sensor, the chrominance signal converter converting the chrominance signal into a chrominance signal of a target display color that has been set by the target display color setting section.

4. (CURRENTLY AMENDED) The image display device as set forth in Claim 32, wherein:

the chrominance signal converter includes a color reproduction section for reproducing the a color to display as an image agreeable with chromatic adaptation characteristics of human by using three primary colors having chromaticities suitable for the external light the output of the sensor, the chrominance signal converter converting the chrominance signal into a chrominance signal of a color reproduced by the color reproduction section.

5. (CURRENTLY AMENDED) ~~The image display device as set forth in Claim 2,~~
~~wherein:~~ An image display device, comprising:

a sensor for sensing light characteristics of external light;

an image display section for displaying an image in accordance with an input of a chrominance signal;

a chrominance signal converter for converting the chrominance signal to be inputted into the image display section, in accordance with the light characteristics of the external light that strikes onto the image display section, wherein the chrominance signal converter converts the chrominance signal into a chrominance signal of a color suitable for an output of the sensor; and

wherein the chrominance signal converter includes (1) a target display color setting section for setting a color to display as an image agreeable with chromatic adaptation characteristics of human, according to the output of the sensor, and (2) a color reproduction section for reproducing a target display color that has been set by the target display color setting section, by using three primary colors having chromaticities suitable for the output of the sensor, the chrominance signal converter converting the chrominance signal into a chrominance signal of a target display color reproduced by the color reproduction section.

6. (CURRENTLY AMENDED) An image display device, comprising: The image display device as set forth in Claim 2, wherein

an image display section for displaying an image in accordance with an input of a chrominance signal; and

a chrominance signal converter for converting the chrominance signal to be inputted into the image display section in accordance with light characteristics of external light incident upon the image display section, the chrominance signal converter including

(1) a color correction coefficient generator for generating a color correction coefficient, in accordance with the light characteristics of the external light output of the sensor, and

(2) a color correction section for correcting the chrominance signal by using the color correction coefficient generated by the color correction coefficient generator.

7. (CURRENTLY AMENDED) The image display device as set forth in Claim 6, wherein:

the color correction coefficient generator includes (1) a target display color setting coefficient generator for generating a target display color setting coefficient as a first color correction coefficient used for setting a target display color, and (2) a color reproduction coefficient generator for generating a color reproduction coefficient as a second color correction coefficient used for color reproduction, based on the information regarding the light characteristics of the external light output of the sensor, and

the color correction section includes (1) a multiplier for calculating a product of (a) the target display color setting coefficient generated by the target display color setting coefficient generator, and (b) the color reproduction coefficient generated by the color reproduction coefficient generator, and (2) a target display color correction section for performing color correction of a chrominance signal, based on a value obtained by the multiplier.

8. (CURRENTLY AMENDED) The image display device as set forth in Claim 30 2, wherein:

the sensor has a function to resolve wavelength characteristics into at least two different types of wavelength regions, and measures wavelength characteristics of the external light, based on output values in the respective wavelength regions.

9. (CURRENTLY AMENDED) An image display device ~~as set forth in Claim 1,~~ further comprising:

an image display section for displaying an image in accordance with an input of a chrominance signal;

919 a chrominance signal converter for converting the chrominance signal to be inputted into the image display section, in accordance with light characteristics of external light that strikes onto the image display section;

a memory for storing ~~in advance~~ the light characteristics of a plurality of types of the external light [[,]]; and

wherein the chrominance signal converter converts the chrominance signal into a chrominance signal of a color suitable for the light characteristics of the external light that are selected and read out from the memory.

10. (Original) The image display device as set forth in Claim 9, wherein:

the memory stores wavelength characteristics of more than two types of wavelength regions of the external light, and outputs the wavelength characteristics as the selected light characteristics of the external light, in accordance with a combination of the stored wavelength characteristics.

11. (CURRENTLY AMENDED) The image display device as set forth in Claim 9, wherein:

the chrominance signal converter includes a target display color setting section for setting the a color to display as ~~an image agreeable with chromatic adaptation characteristics of human~~, based on the light characteristics of the external light selected from the memory, the chrominance signal converter converting the chrominance signal into a chrominance signal of a target display color that has been set by the target display color setting section.

12. (CURRENTLY AMENDED) The image display device as set forth in Claim 9, wherein:

the chrominance signal converter includes a color reproduction section for reproducing the a color to display as ~~an image agreeable with chromatic adaptation characteristics of human~~, by using three primary colors having chromaticities suitable for the light characteristics of the external light selected from the memory, the chrominance signal converter converting the chrominance signal into a chrominance signal of a color reproduced by the color reproduction section.

13. ((CURRENTLY AMENDED) The image display device as set forth in Claim 9, wherein:

the chrominance signal converter includes (1) a target display color setting section for setting the a color to display as ~~an image agreeable with chromatic adaptation characteristics of human~~, based on the light characteristics of the external light selected from the memory, and (2) a color reproduction section for reproducing a target display color that has been set by the target display color setting section, by using three primary colors having chromaticities suitable for the output of the memory, the chrominance signal converter converting the chrominance signal into a chrominance signal of the target display color reproduced by the color reproduction section.

14. (Original) An image display device as set forth in Claim 9, further comprising:
a sensor for sensing the light characteristics of the external light,
wherein the chrominance signal converter selectively performs (1) conversion of a chrominance signal based on an output of the sensor, or (2) conversion of a chrominance signal based on the light characteristics of the external light selected from the memory.

15. (Original) The image display device as set forth in Claim 14, wherein:
the chrominance signal converter performs the conversion of the chrominance signal based on the light characteristics of the external light selected from the memory, when an illuminance output, which is one of types of the outputs of the sensor, exceeds a certain value.

16. (Original) The image display device as set forth in Claim 9, wherein:
the memory stores in advance a plurality of types of characteristics of the external light and a plurality of color correction coefficients that vary depending on the light characteristics of the external light; and
the chrominance signal converter includes (1) a color correction coefficient generator for reading out a color correction coefficient stored in the memory, based on the selected light characteristics of the external light, and (2) a color correction section for correcting the chrominance signal by using the color correction coefficient that is read out from the memory by the color correction coefficient generator.

17. (CURRENTLY AMENDED) An electronic apparatus, which has an image display device, comprising:
an image display section for displaying an image in accordance with an input of a chrominance signal; and

a chrominance signal converter for converting the chrominance signal to be inputted into the image display section, in accordance with light characteristics of external light incident upon that strikes onto the image display section, the chrominance signal converter including a target display color setting section which uses information regarding the light characteristics of the external light to generate a target display color chrominance signal indicative of a color to display on the image display section for providing an image which agrees with human chromatic adaptation characteristics.

18. (CANCELLED).

19. (CANCELLED).

119
20. (CURRENTLY AMENDED) An image display method comprising converting a chrominance signal to be inputted into an image display section, in accordance with light characteristics of external light that strikes onto the image display section that displays an image in accordance with an input of a chrominance signal, The image display method as set forth in Claim 18, wherein the chrominance signal is converted into a chrominance signal of a color suitable for the light characteristics of the external light that are selected and read out from among light characteristics of a plurality of types of external light, which are stored in a memory in advance.

21. (CANCELLED)

22. (CANCELLED)

23. (CANCELLED)

24. (ORIGINAL) The image display method as set forth in Claim 20, wherein the conversion of the chrominance signal is carried out based on a color to display, which is set according to the light characteristics of the external light and in consideration of color adaptation characteristics of human.

25. (Original) The image display method as set forth in Claim 20, wherein the conversion of the chrominance signal is carried out based on a color reproduced by using three primary colors having chromaticities suitable for the light characteristics of the external light.

26. (CURRENTLY AMENDED) The image display method as set forth in Claim 20, wherein a color is set, according to the light characteristics of the external light, as an image which agrees ~~agreeable~~ with human chromatic adaptation characteristics ~~of human~~, the color is reproduced by using three primary colors having chromaticities suitable for the light characteristics of the external light, and the conversion of the chrominance signal is carried out based on the reproduced color.

27. (NEW) The image display device of claim 3, further comprising means for supplying the information regarding the light characteristics.

28. (NEW) The image display device of claim 27, wherein the means for supplying the information regarding the light characteristics comprises a sensor.

29. (NEW) The image display device of claim 6, further comprising means for supplying the information regarding the light characteristics.

30. (NEW) The image display device of claim 29, wherein the means for supplying the information regarding the light characteristics comprises a sensor.

31. (NEW) The image display device of claim 29, wherein the means for supplying the information regarding the light characteristics comprises a memory for storing in advance the light characteristics of a plurality of types of the external light, and wherein the chrominance signal converter converts the chrominance signal into a chrominance signal of a color suitable for the light characteristics of the external light that are selected and read out from the memory.

32. (NEW) The image display device as set forth in Claim 31, wherein: the memory stores wavelength characteristics of more than two types of wavelength regions of the external light, and outputs the wavelength characteristics as the selected light characteristics of the external light, in accordance with a combination of the stored wavelength characteristics.

419 33. (NEW) The image display device as set forth in Claim 31, wherein: the chrominance signal converter includes a target display color setting section which uses information regarding the light characteristics of the external light to generate a target display color chrominance signal indicative of a color to display on the image display section for providing an image which agrees with human chromatic adaptation characteristics.

34. (NEW) The image display device as set forth in Claim 33, wherein: the chrominance signal converter includes a color reproduction section for reproducing the color to display by using three primary colors having chromaticities suitable for the light characteristics of the external light selected from the memory, the chrominance signal converter converting the chrominance signal into a chrominance signal of a color reproduced by the color reproduction section.

35. (NEW) An electronic apparatus, which has an image display device, comprising:
an image display section for displaying an image in accordance with an input of a chrominance signal; and
a chrominance signal converter for converting the chrominance signal to be inputted into the image display section, the chrominance signal converter including
(1) a color correction coefficient generator for generating a color correction coefficient in accordance with the information regarding the light characteristics of the external light, and
(2) a color correction section for correcting the chrominance signal by using the color correction coefficient generated by the color correction coefficient generator.

36. (NEW) A method of operating an image display device comprising:
obtaining information regarding light characteristics of external light incident upon a screen of the image display device;
using an input chrominance signal and the information regarding the light characteristics of external light to generate a target display color chrominance signal indicative of a color to display for providing an image which agrees with human chromatic adaptation characteristics.

37. (NEW) The method of claim 36, further comprising obtaining the information regarding the light characteristics of external light from a sensor.

38. (NEW) The method of claim 36, further comprising:
obtaining the information regarding the light characteristics of external light from a memory in which are stored the light characteristics of a plurality of types of external light;

converting the chrominance signal into a chrominance signal of a color suitable for the light characteristics of the external light that are selected and read out from the memory.

39. (NEW) A method of operating an image display device comprising:
obtaining information regarding light characteristics of external light incident upon a screen of the image display device;

using a color correction coefficient generator to generate a color correction coefficient;

correcting an input chrominance signal using the color correction coefficient; and
applying the corrected input chrominance signal to an image display section.

40. (NEW) The method of claim 39, further comprising obtaining the information regarding the light characteristics of external light from a sensor.

41. (NEW) The method of claim 39, further comprising:
obtaining the information regarding the light characteristics of external light from a memory in which are stored the light characteristics of a plurality of types of external light;

converting the chrominance signal into a chrominance signal of a color suitable for the light characteristics of the external light that are selected and read out from the memory.

IN THE DRAWINGS

The attached replacement sheet(s) of drawing(s) include change(s) to Fig. 1, 7-14, and Fig. 17A - Fig. 17E.

Attachment: Replacement Sheet(s)